



NOTES: ROADSIDE DITCH SHALL NOT BE FILLED IN. SURFACE OF DRIVEWAY MUST FOLLOW EXISTING GROUND CONTOUR AND MAINTAIN EXISTING GROUND ELEVATION WITHIN ROAD RIGHT-OF-WAY.

SURFACE OF DRIVEWAY APRON ABUTTING THE ROADWAY MUST BE A MIN. OF 1" BELOW THE EDGE OF PAVEMENT.

NOTES: ONLY ONE DRIVEWAY IS PERMITTED PER PARCEL. ADDITIONAL DRIVES MAY BE ALLOWED PURSUANT TO THE ALLEN COUNTY ACCESS MANAGEMENT REGULATIONS.

FOR CONCRETE DRIVEWAYS SEE STANDARD DRAWING DW-1 FOR THICKNESS OF CONCRETE.

DRIVE PIPE MUST BE 4 FT. PAST EACH SIDE OF DRIVEWAY REGARDLESS OF PIPE PLACEMENT IN THE ROADSIDE DITCH.

REVISIONS		ALLEN COUNTY, OHIO	
NO.	BY	DATE	COUNTY ENGINEER
1	6-12-07	BT	MINIMUM DRAINAGE & DRIVEWAY STANDARDS
2	9-21-00	BT	RESIDENTIAL DRIVES
3	1-1-04	DL	STANDARD CONSTRUCTION DRAWING DW-2
4	10-5-06	ZIG	DRAWN BY: Z.J.G. APPROVED BY: B.E. RHODES
5	5-21-10	DL	
6	1-16-13	RM	
7	5-16-16	RM	
8			